

Surgeflex 12 and 16

Portable cable test and fault location system for medium and low voltage power cables



- **Safe and fast fault location with latest Teleflex SX technology**
- **High surge energy for effective pinpoint locating**
- **Various fault location methods included**

DESCRIPTION

The Surgeflex unit is a mobile system for testing and fault locating on low and medium voltage cables. The powerful ARM[®] (Arc Reflection Method) is used to prelocate high resistance faults. Conditioning faults – if necessary – is possible by short-term burning in all voltage levels.

The Teleflex SX is operated by the new touchscreen and the well-proven control knob functionality. The interface is shown on a bright, sharp 10.4" display. The Teleflex SX is specially adapted to deal with the rapidly unfolding events that occur during power cable fault location. The easyGO operation is reduced to the essential steps, most of which run automatically. The new hardware uses improved parameters including sampling frequency, pulse width and impulse amplitude to guarantee larger ranges and the highest resolution.

The high surge energy provides the necessary power to accurately pinpoint cable faults by using the acoustic method. Big wheels make the unit suitable for easy operation in the field. Connecting cables for earthing, mains, and HV are conveniently accessible at the rear of the unit.

Modes

- Symmetrical / asymmetrical reflection measurement
- Difference measurement / comparison
- ARM[®] Arc Reflection Methods
- ICE impulse current decoupling methods
- DECAY Travelling wave method
- IFL Intermittent Fault Location

TECHNICAL DATA*

Teleflex SX

Range	20 m ... 160 km @ v/2 = 80 m/μs
Pulse width	20 ns ... 10 μs
Pulse amplitude	10 ... 50 V
Accuracy of the distance measurement	± 0,2 % of the measuring range
Resolution	0.1 m @ v/2 80 m/μs, 1.0 cm @ v/2 < 40 m/μs
Sample rate	Up to 400 MHz
Gain	-37 ... +37 db
De-attenuation	0 ... +22 dB for ProRange (adjustable 0 ... 100 %)
Propagation velocity v/2	10 ... 149,9 m/μs, ft/μs or nvp
Dynamic range	> 80 dB
Output impedance	50 Ω
Compensation	10 Ω ... 500 Ω, adjustable
ARM trigger	Automatic adaptation by ΔU Trigger or L↑H edge trigger
ARMslide	15 measurements in one ARM shot
Dead zone	None
Voltage proof input	< 400 V, operation only with separation filter
Display	10.4" color TFT XGA 1024x768, touchscreen, 600 cd/m2, LED-Backlight, dimmable
Data storage	2 GB mSATA for program and data
Connectors	Ethernet, USB, BNC, CAN (LON optional)
Protection class	IP 65 closed, IP 54 open lid
Supply	110 ... 240 V, 50/60 Hz, 30 VA 10 V ... 17 V DC, 3.8 A
Dimensions (W x H x D)	362 x 195 x 306 mm (option 19", 6 HU)
Weight	10 kg
Operation temperature	-10 °C ... +50 °C
Storage temperature	-20 °C ... +60 °C

HV module

	SPG 12	SPG 16
Testing	0 ... 17 kV	0 ... 24 kV
Surge	0 ... 3 kV; 1100 J 0 ... 6 kV; 1100 J 0 ... 12 kV; 1100 J	0 ... 4 kV; 2000 J 0 ... 8 kV; 2000 J 0 ... 16 kV; 2000 J
Burning	0 ... 12 kV; 200 mA	0 ... 16 kV; 200 mA
Surge rate	3 ... 10 sec, single pulse	
Sheath fault locating	0 ... 5 kV, 120 mA	
IP-grade	IP 20	
Protection class	I	
Operation temperature	-10 °C ... +50 °C	
Weight	approx. 135 kg	

Connection cables and supply

Connection cable	6 m HV test lead
Mains supply	230 V; 50 Hz / 2 kVA Isolation transformer 2 kVA (ca. 26 kg) (opt. 110 V step-up transformer)
Dimensions (W x H x D)	800 x 1280 x 800 mm

ORDERING INFORMATION

Product	Order no.
Surgeflex 12-1100 consisting of: Surge Unit SPG 12, 3/6/12 kV, 1100 J with ARM & ICE 12 kV, test voltage up to 17kV, 230V AC input, set of cables, trolley, separation transformer 2000VA, TFX SX	SFX12P-1100-P-SX-N
Surgeflex 16-2000 consisting of: Surge Unit SPG 16, 4/8/16 kV, 2000 J with ARM & ICE 16 kV, test voltage up to 24kV, 230V AC input, set of cables, trolley, separation transformer 2000VA, TFX SX	SFX16P-2000-P-SX-N
Options:	
digiPHONE+	1003316-S
digiPHONE+ NT Set	1003317-S
ESG NT Set	1004629-S

* We reserve the right to make technical changes.

GERMANY

Megger GmbH
Obere Zeil 2
D-61440 Oberursel
T +49 6171 92987 0
F +49 6171 92987 19
info@megger.de

Seba Dynatronic
Mess- und Ortungstechnik GmbH
Dr.-Herbert-lann-Str. 6
96148 Baunach
T +49 (0) 9544 680
F +49 (0) 9544 2273
team.dach@megger.de

Hagenuk KMT
Kabelmesstechnik GmbH
Röderaue 41
01471 Radeburg
T +49 (0) 35208 840
F +49 (0) 35208 84249
team.dach@megger.de

CERTIFICATION ISO

Registered to ISO 9001 Cert. no. 000677 QM08
SFX12_SFX16_DS_EN_V01
www.megger.de
Megger is a registered trademark